

CE

RoHS

MAKE IN INDIA

SD-SN-NH3-M

Ammonia Electrochemical Sensor with Modbus RS485

- Sensor with Electrochemical Sensor element – (0-1000 ppm)
- Isolated Modbus RTU RS485 Port (Soft Configurable)
- Option for Offset Calibration using Modbus Register
- Input Power Source – 12-24V DC
- Enclosure Size – 85 x 85 x 35mm

SD-SN-NH3-W

Ammonia Electrochemical Sensor with Wi-Fi

- Sensor with Electrochemical Sensor element – (0-1000 ppm)
- Communication Modes
- Modbus over Wi-Fi, MQTT over Wi-Fi, ASCII over Wi-Fi
- Input Power Source – 12-24V DC
- Enclosure Size – 85 x 85 x 35mm

SD-SN-NTC-M

NTC Based Temperature Sensor with Modbus RS485

- NTC Type 3 10k based Sensor Probe
- Isolated Modbus RTU RS485 Port (Soft Configurable)
- Option for Offset Calibration using Modbus Register
- Input Power Source – 12-24V DC
- Enclosure Size – 85 x 85 x 35mm

SD-SN-PM25/1/10-M

Particulate Matter Air Quality Sensor with Modbus RS485

- Sensor with PM 2.5, PM1.0 and PM10 Detection
- PM 2.5 – Range – 0 – 1000 ug/m3 Accuracy – 5 ug/m3 10 % m.v
- PM 1.0 – Range – 0 – 1000 ug/m3 Accuracy – 5 ug/m3 10 % m.v
- PM 10 – Range – 0 – 1000 ug/m3 Accuracy – 25 ug/m3 25 % m.v
- Isolated Modbus RTU RS485 Port (Soft Configurable)
- Input Power Source – 12-24V DC
- Enclosure Size – 85 x 85 x 35mm

SD-SN-PM25/1/10-M-D

Particulate Matter Air Quality Sensor with Modbus RS485 and 7

- Segment Display
- Sensor with PM 2.5, PM1.0 and PM10 Detection
- PM 2.5 – Range – 0 – 1000 ug/m3 Accuracy – 5 ug/m3 10 % m.v
- PM 1.0 – Range – 0 – 1000 ug/m3 Accuracy – 5 ug/m3 10 % m.v
- PM 10 – Range – 0 – 1000 ug/m3 Accuracy – 25 ug/m3 25 % m.v
- Isolated Modbus RTU RS485 Port (Soft Configurable)
- Input Power Source – 12-24V DC
- Enclosure Size – 85 x 85 x 35mm

YOUR PARTNER IN Digitization, Digitalization, Digital Transformation

www.shreemdigital.in • shreemdigi@gmail.com • Ahmedabad, Gujarat • +91 8332022161 • +91 9825022644